



Ordering Information

F73	2	3		1	4		
Style F73 = Rectangle	Lamps 2 = Lamps	Length 3 = 3 Foot	Wattage 7 = 39W 8 = 39W Dimming	Voltage 1 = 120V	Type 4 = Louver	Color AL = Aluminum WH = White	Mounting F = Floor Stand P = Panel Bolt-on E = Expandable Bracket B = Binder Bin

Example = F7323714ALP

Features

Housing: High purity extruded aluminum, a portion from recycled material.

F7300: Block shape with solid sides.

Housing end: Die-cast aluminum, welded to the housing.

Finish: Powder coat baked enamel. Standard colors: white or aluminum.

Shielding: Louver.

Lamp: 2x39 watt T5HO lamps (included).

Ballast: Electronic and meets ANSI starting, end of life protection, THD and sound rating specifications.

Switching: On/off switch on stem. Optional cord switch available.

Wiring: 3-wire cord with grounded low profile plug. Minimum length 9 feet.

Listing: UL/cUL listed.

Job Information


Type:

Job Name:

Cat. No.:

Lamp(s):

Notes:



Candlepower Curve


Report No:
ITL54672.IES.MOD

Catalog No:
F7323714xxx

Lamps:
2-F39T5/HO

Lumens:
3500 each


Efficiency:
82.5%



Coefficients of Utilization


% Effective Ceiling Cavity Reflectance									
	80			70			50		
% Wall Reflectance									
	50	30	10	50	30	10	50	30	10
0	62	62	62	56	56	56	44	44	44
1	55	53	51	49	47	46	39	38	37
2	48	45	42	43	41	38	35	33	31
3	42	38	35	38	35	32	31	28	26
4	38	33	30	34	30	27	28	25	23
5	34	29	26	31	27	24	25	22	20
6	30	26	22	28	24	21	22	19	17
7	27	23	20	25	21	18	20	17	15
8	25	20	17	23	19	16	18	16	14
9	23	18	15	21	17	14	17	14	12
10	21	17	14	19	15	13	16	13	11

Zone	Zonal Lumen Summary		
	Lumens	% Barelamp	% Luminaire
0-90	1809	25.8	31.3
90-180	3964	56.6	68.7
0-180	5773	82.5	100.0




Binder Bin Mount Weighted Base

Weighted base allows fixture to sit atop shelves or overhead cabinets.
Not recommended for use in seismic areas.




Panel Mount (Bolt-On)

Bolts to the top of furniture systems or short walls.
A small steel bracket is bolted through the top cap.
The stem assembly slides onto this bracket and is held in place with hidden set screws.



Expandable Bracket

This adjustable bracket clamps onto furniture systems ranging from 2" to 4" thick.



Floor Stand

Job Information

Type:

Lightolier a Genlyte company

www.lightolier.com

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710

We reserve the right to change details of design, materials and finish.

© 2007 Genlyte Group LLC • A0107